

EVG 50/2,5

Order No.: 15025200

Specification Sheet

Type	Electronic convertor for high-voltage luminous discharge tubes according to EN 50107. Suitable for indoor and outdoor systems. Limited suitability for flash operation.	CE
Weight	0.750 kg	
Radio interference suppression	According to VDE 0875, Part 2A1 (EN 55015)	
Temperatures	Ambient temperature range: -25 to +65°C Temperature limit: +80°C (max. ambient temp. that the convertor is able to withstand for a short period of time without being destroyed)	
Housing	Polystyrene shell Standard colour: white Filling compound: polyurethane (black)	
Class of protection	I	
Degree of protection	IP 65	

Primary Data	
Mains voltage	230 Volt, +/- 10 %, 50 / 60Hz
Current consumption	Depends on the connected tube load; max. 0.65 Amp. cos phi 0.95

Protective Equipment	
Safety fuse	Integrated 1 Amp. melting fuse offering protection against internal short circuits.
Earth leakage trip	(acc. to EN 50107) integrated in the convertor
Open circuit protection	(acc. to EN 50107) integrated in the convertor (optional) (The open circuit protection must be ordered separately.)

Caution:
 The installation instructions must be observed when using the convertors!

Secondary Data

2,500 Volt with 50 mA constant current, symmetrical alternating current, load-dependent operating frequency, 16-20 kHz, centrally earthed secondary winding.

Secondary current tolerance:
 -5/+10% (of rated value)

Suitable for blue discharge tubes.

Only partly suitable for red discharge tubes due to an occasional jelly bean effect.

Connectable tube lengths (in meter):

Blue discharge (outdoor)						
Diameter	10	12	15	18	20	22
1 Syst.	3.0	3.7	4.5	5.3	5.7	6.2
2 Syst.	2.6	3.2	3.9	4.6	5.0	5.4
3 Syst.	2.1	2.7	3.3	3.9	4.2	4.5
4 Syst.	1.7	2.2	2.7	3.1	3.4	3.7
5 Syst.	1.3	1.6	2.2	2.4	2.6	2.8

Blue discharge (indoor)						
Diameter	10	12	15	18	20	22
1 Syst.	3.6	4.5	5.4	6.4	6.9	7.5
2 Syst.	3.2	4.0	4.8	5.7	6.1	6.6
3 Syst.	2.8	3.5	4.2	5.0	5.3	5.8
4 Syst.	2.4	3.0	3.6	4.2	4.6	5.0
5 Syst.	2.0	2.5	3.0	3.7	3.8	4.1

The values given represent the maximum connectable tube lengths which must not be exceeded. Shorter tube lengths, however, may be connected without any restrictions. The tube lengths are calculated on the basis of the 'Filling Pressure Recommendations for Fluorescent Tubes' published by the German *Fachverband Lichtwerbung*.

Technical modifications reserved.

Housing dimensions



170x53x44mm

Housing colour: white
 All dimensions in millimetres

