

LED Converter C50/160

Type	C50/160
Operating mode:	constant current
Output current:	50 mA
Output voltage:	max. 160 V
Output power (max.):	8 W
Dimmable:	no
No. of LEDs (white, blue, green):	10 to 50 LEDs
No. of LEDs (red, yellow, orange):	15 to 75 LEDs
Input voltage:	180–260 V AC / 50–60 Hz
Input current (max.):	0.035 A
Power factor:	> 0.9
No-load power:	< 0.2 W
Efficiency:	> 85%
Protection class:	II
Degree of protection:	IP67
EMC emission:	EN 55015, EN 61000-3-2
EMC immunity:	EN 61547

Other data	
Ambient temperature:	-25 °C to +55 °C
Housing:	Housing shell made of rigid PVC Fire protection class B1 Polyurethane potting compound
Dimensions (L x W x H):	152 x 14 x 11 mm
Weight:	60 g
Conformity:	CE, RoHS
Article number:	5 2530 046

LED Converter C100/160

Type	C100/160
Operating mode:	constant current
Output current:	100 mA
Output voltage:	max. 160 V
Output power (max.):	16 W
Dimmable:	no
No. of LEDs (white, blue, green):	10 to 50 LEDs
No. of LEDs (red, yellow, orange):	10 to 75 LEDs
Input voltage:	180–260 V AC / 50–60 Hz
Input current (max.):	0.070 A
Power factor:	> 0.9
No-load power:	< 0.2 W
Efficiency:	> 85%
Protection class:	II
Degree of protection:	IP67
EMC emission:	EN 55015, EN 61000-3-2
EMC immunity:	EN 61547

Other data	
Ambient temperature:	-25 °C to +55 °C
Housing:	Housing shell made of rigid PVC Fire protection class B1 Polyurethane potting compound
Dimensions (L x W x H):	152 x 14 x 11 mm
Weight:	60 g
Conformity:	CE, RoHS
Article number:	5 1201 006

Note: Input and output are not galvanically isolated from each other!
The converters are short-circuit- and open-circuit-proof (no switch-off).

Dimensions:
152 x 14 x 11 mm (L x W x H)



Input cable:
H03VV-F, 2 x 0.75 mm²
Length: 1,000 mm

Output cable:
X03VV-F, 2 x 0.75 mm²
Length: 1,000 mm

Core colours and polarity:
Red: positive
Black: negative



Technical modifications reserved. Content is protected by copyright.

January 2019 C50-160-e/01/2019